



<b>Name</b>	R4
<b>Sensor Type</b>	1/3"CMOS
<b>Display Resolution</b>	2560×1440(4.0Megapixels), 2304×1296(3.0Megapixels)
<b>Frame Rate</b>	25fps
<b>IR CUT</b>	√
<b>Minimum Illumination</b>	0 Lux (With IR Illuminator)
<b>Lens Type</b>	f: 4.0mm; F: 2.1
<b>Diagonal Angle of View</b>	75°
<b>Horizontal Angle of View</b>	67°(Pan/Tilt Angle: H=300°V=100°)
<b>IR Range</b>	13pcs IR-LEDs, IR range up to 8 meters (26.2feet)
<b>Ethernet</b>	One 10/100Mbps RJ45 port
<b>WPS</b>	√
<b>Wireless Standard</b>	IEEE802.11b/g/n
<b>Wireless Security</b>	WEP, WPA, WPA2
<b>P2P</b>	√
<b>External I/O</b>	N/A
<b>802.3af PoE</b>	N/A
<b>External Card Slot</b>	128G Micro SD card
<b>Video Format</b>	H.264
<b>Multi Stream</b>	Dual stream
<b>Motion Detection</b>	√
<b>Scheduled Recording</b>	√
<b>Built-in DDNS Server</b>	√
<b>Browser Supported</b>	IE8 and above version; Firefox; Chrome; Safari
<b>OS Supported</b>	Windows XP, 7, 8; Mac OS; iOS, Android
<b>Infrared Mode</b>	Automatic or manual
<b>Day and Night</b>	√
<b>Firewall</b>	Supports IP Filtering
<b>Two-way Audio</b>	√
<b>Built-in Microphone</b>	√
<b>External Microphone Input</b>	N/A
<b>Built-in speaker</b>	√
<b>External Speaker Output</b>	N/A
<b>Dimensions(mm)</b>	74 (L) × 74 (W) × 119 (H)
<b>Power Adapter</b>	5V/2A
<b>Power Consumption</b>	<6W
<b>Operating Temperature</b>	-10°C ~ 55° (14°F ~ 131°F)
<b>Operating Humidity</b>	20% ~ 85% non-condensing
<b>Certificate</b>	CE, FCC, RoHS